

When your feed water has a hardness of over 5 degrees German hardness DH (over 89 mg CaCO₃ per litre) we strongly advise to install a water softener. The water softener avoids calcic deposits in the tubing and internals of heating equipment, washing machines, fog systems and similar equipment. Use of a water softener highly improves the lifetime of your equipment.

Reldair supplies water softeners where the components are produced under own supervision to guarantee the required quality.

Because of the use of dry salt an exact quantity of salty water is produced each cycle to minimize consumption of salt and to avoid growth of bacteria.



Unique characteristics on Reldair water softeners

Reldair water softeners for fog systems are equipped with the newest technology from the water treatment industry and optimized in the combined use.

Reldair softeners have a unique control system, which suits them for centralized softening and causes no constraints to generic drinking water guidelines. Besides these they were designed on minimized salt and rinsing water usage.

We supply our softeners including bypass- and connection hoses and -kit. This makes the installation very easy and self-explaining. Controlled by the integrated microprocessor makes the programming very easy

TECHNICAL DATA	RW11	RW14	RW17	RW25	RW40
Volume (litre)	11	14	17	20	30
Capacity per hour (m ³ /h)	1,9	1,9	2,0	2,0	2,8
Salt tank size (kg)	35	50	70	105	100
Dimensions (LxWxH)	30x48x65	30x48x84	30x48x106	46x124 ØxH	46x124 ØxH
Max. temperature (°C)	49				
Water pressure (min-max)	1,4 – 8,6 bar				
Electrical connection	230 -24 VDC				
Price	€ 1.200,-	€ 1.250,-	€ 1.300,-	€ 1.350,-	€ 1.625,-